



### LOCAL STREETS:

AC - 6" CLASS "C" ASPHALTIC CONCRETE,  
AB - 4" (1-1/2" - 0") AGGREGATE BASEROCK

OR

AC - 8" CLASS "C" ASPHALTIC CONCRETE

### MINOR COLLECTOR STREETS:

AC - 7" ASPHALTIC CONCRETE,  
AB - 4" (1-1/2" - 0") AGGREGATE BASEROCK

OR

AC - 9" CLASS "C" ASPHALTIC CONCRETE

### MAJOR COLLECTOR STREETS:

AC - 9" CLASS "C" ASPHALTIC CONCRETE,  
AB - 4" (1-1/2" - 0") AGGREGATE BASEROCK

### NOTES:

1. JOINTS TO BE TACK AND SANDED.
2. ASPHALT PLACED IN MAX. 3' LIFTS EACH COMPACTED TO 92% MIN.
3. SAWCUT SHALL BE TAC COATED WITH BITUMINUS ASPHALT EMULSION.



ENGINEERING DEPARTMENT  
13125 S.W. HALL BLVD.  
TIGARD, OREGON 97223  
VOICE: (503) 639-4171  
FAX: (503) 684-7297

APPROVED BY:

AGUSTIN P. DUENAS

CITY ENGINEER

MARCH 1998

APPROVAL DATE

## PAVEMENT DIG-OUT AND REPAIR

NO SCALE

DWG. NO.

182